


Flexible Fused Silica Capillary Tubing

- **TSP:** Standard Polyimide Coating
- **TSG:** High Temperature Polyimide Coating

TSP & TSG Standard Products

Product Descriptor	ID µm	OD µm	CT* µm
TSP002150	002 ± 01	150 ± 06	12
TSP005150	005 ± 02	150 ± 06	12
TSP005375	005 ± 02	363 ± 10	20
TSP010150	010 ± 02	150 ± 06	12
TSP010375	010 ± 02	363 ± 10	20
TSP015150	015 ± 02	150 ± 06	12
TSP015375	015 ± 02	363 ± 10	20
TSP020090	020 ± 02	090 ± 06	12
TSP020150	020 ± 02	150 ± 06	12
TSP020375	020 ± 02	363 ± 10	20
TSP025150	025 ± 02	150 ± 06	12
TSP025375	025 ± 02	363 ± 10	20
TSP030150	030 ± 02	150 ± 06	12
TSP030375	030 ± 02	363 ± 10	20
TSP040105	040 ± 03	105 ± 06	12
TSP040150	040 ± 03	150 ± 06	12
TSP040375	040 ± 03	363 ± 10	20
TSP050150	050 ± 03	150 ± 06	12
TSP050192	050 ± 03	186 ± 06	16
TSP050375	050 ± 03	363 ± 10	20
TSP075150	075 ± 03	150 ± 06	12
TSP075200	075 ± 03	193 ± 07	12
TSP075375	075 ± 03	363 ± 10	20
TSP100170	100 ± 04	164 ± 06	12
TSP100200	100 ± 04	193 ± 07	12
TSP100245	100 ± 04	238 ± 07	16
TSP100375	100 ± 04	363 ± 10	20
TSP150375	150 ± 04	363 ± 10	20
TSP180350	180 ± 06	360 ± 10	18
TSP200350	200 ± 06	360 ± 10	18
TSP250350	250 ± 06	360 ± 10	18
TSP320450	320 ± 06	435 ± 10	18
TSP450660	450 ± 06	673 ± 15	24
TSP530660	536 ± 06	665 ± 15	24
TSP530700	530 ± 10	700 ± 20	24
TSP700850	700 ± 10	850 ± 20	24
TSG250350	250 ± 06	350 ± 15	20
TSG320450	320 ± 06	435 ± 15	18
TSG530660	536 ± 06	673 ± 25	30




TSP Characteristics

- ◀ Standard polyimide coating
- ◀ Synthetic fused silica
- ◀ 100% proof tested for strength
- ◀ Operation up to 350°C

TSG Characteristics

- ◀ High temperature polyimide coating
- ◀ Synthetic fused silica
- ◀ 100% proof tested for strength
- ◀ Operation up to 400°C



Explore Our Other Unique Capillary Products and Capabilities

- ◀ Custom ID & OD sizes and tolerances
- ◀ Internal and external coatings
- ◀ Shaped cross-sectional geometries
- ◀ Precision cleaving
- ◀ Laser cutting
- ◀ Windowing
- ◀ Custom arrays and assemblies

Online Ordering

Products with ID of 320µm and smaller are available for immediate online ordering in quantities of 10m, 25m, or 50m. Go to www.polymicro.com to buy your capillary tubing today.

* CT is Coating Thickness per slide; value is nominal.